



Areas of Application

For lockout applications where more than one safety padlock has to be attached. Serves as a multiplier for padlock holes, makes six for one, so that it allows up to six workers to lock out a single energy source.

Details

- Available in 1"/2.54 cm and 1.5"/3.81 cm diameter jaws
- Available with or without interlocking tabs to prevent unauthorized opening
- Vinyl coated high tensile steel

Material

- Flanks: Steel, nickel-plated with dip vinyl coating
- Rivet: Aluminum

Dimensions

- | | | | | |
|---------|----------------|--------------|--------------|------------------|
| • H701: | Length: 115 mm | Width: 45 mm | Depth: 10 mm | Inner Ø: 25,4 mm |
| • H702: | Length: 128 mm | Width: 60 mm | Depth: 10 mm | Inner Ø: 38,1 mm |
| • H711: | Length: 118 mm | Width: 45 mm | Depth: 12 mm | Inner Ø: 25,4 mm |
| • H712: | Length: 131 mm | Width: 60 mm | Depth: 12 mm | Inner Ø: 38,1 mm |

Temperature Range

- Steel: -35°C to +177°C (-30°F to +350°F)
- Vinyl coating: -35°C to +95°C (-30°F to +200°F)
- Stainless steel rivet: -30°C to +175°C (-20°F to +350°F)

Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart only.

Chemical	Grade
Mineral lubricants	Conditionally resistant
Aliphatic hydrocarbons	Conditionally resistant
Aromatic hydrocarbons	Conditionally resistant
Gasoline	Resistant
Weak mineral acids	Conditionally resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Conditionally resistant
Strong organic acids	Not resistant
Oxidizing acids	Not resistant
Weak bases	Resistant
Strong bases	Conditionally resistant
Trichloroethylene	Conditionally resistant
Perchloroethylene	Conditionally resistant
Acetone	Conditionally resistant
Alcohols	Conditionally resistant
Hot water (hydrolysis resistance)	Resistant
UV light and weather	Conditionally resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.