



E233

E218



Areas of Application

E218 and E233 are the perfect choice for securing screw-type fuses. Thanks to the stepped thread diameters at the bottom, each locking device covers two standard screw threads: E218 for E14 and E18 system and E233 for E27 and E33 system.

Details

- Includes a handy special yellow key to place or remove the device. The key can be stored on the fitted shackle if necessary.
- Holds 1 padlock or can be secured in series by help of a cable lock.

Material

- Body, key: ABS

Dimensions



E218:

Height: 52 mm (w/o key)
75 mm (w/ key)
Width: 25 mm Ø (w/o key)
35 mm (w/ key)
Depth: 25 mm Ø

E233:

Height: 61 mm (w/o key)
84 mm (w/ key)
Width: 40 mm Ø
Depth: 40 mm Ø

Yellow key:

Height: 66 mm
Width: 35 mm
Depth: 18 mm

Temperature Range

- -40°C to +105°C (-40°F to +221°F)

Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only.

Chemical	Grade
Mineral lubricants	Resistant
Aliphatic hydrocarbons	Resistant
Aromatic hydrocarbons	Not resistant
Gasoline	Resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Resistant
Strong organic acids	Conditionally resistant
Oxidizing acids	Not resistant
Weak bases	Resistant
Strong bases	Not resistant
Trichloroethylene	Not resistant
Perchloroethylene	Conditionally resistant
Acetone	Conditionally resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Conditionally resistant
UV light and weather	Resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.