

SKG-IKOB PRODUCTCERTIFICATE

466.312.08

Date of issue: 17-05-2021



Certificate holder

ABUS Pfaffenhain GmbH
Fabrikstraße 1
D-09387 Jahnsdorf
T: +49 (0) 37296 7130
E: info@abus-pfaffenhain.de
I: www.abus-pfaffenhain.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder with non lockable knob

delivered under logo / brand:

PFAFFENHAIN / ABUS

delivered under type- and / or article number:

M12R430 , D12R430 , P12R430 , X12R430 , XL2L430

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

ABUS Pfaffenhain GmbH
Number: 466.312.08

page 2 of 2

1. PRODUCT

euro profile cylinder with non lockable knob

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation
Construction: double, with push-knob OR standard knob
with OR without activation pawl on the 2nd key option
with OR without fracture line
System: horizontal key profile 1 row 6 mechanical operated retainers +
1 row of 6 blockelements
Material: cylinder body: brass with various coatings
Dimension: 17 mm profile from 28 mm in various extensions per 5 mm
Fixing: 1 steel bolt M5, length . backset + 10 mm
Intended use: in combination with cylinder mortice locks and security furniture.
Pay Attention!
This cylinder achieves only the SKG-star rating if
a door element (including side window), wherein
at least P4A glass has been applied,
OR in a door element (including side window) with
a section filling without a view on the knob.
A wooden door element (including side window) with
a view to the "standard" turning knob, should be provided with
a SKG (V) certified anti-drill / manipulation device.

3. DELIVERY

The delivery includes an installation instruction:
EK-DR-0051-06.2020
VERPA015-042020

4. PERFORMANCES

A euro profile cylinder with non lockable knob according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).

SKG-IKOB PRODUCTCERTIFICATE 466.312.07

Date of issue: 17-05-2021



Certificate holder

ABUS Pfaffenhain GmbH
Fabrikstraße 1
D-09387 Jahnsdorf
T: +49 (0) 37296 7130
E: info@abus-pfaffenhain.de
I: www.abus-pfaffenhain.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder

delivered under logo / brand:

Pfaffenhain / ABUS

delivered under type- and / or article number:

M12R410 , D12R410 , P12R410 , X12R410 , XL2L410
M12R452 , D12R452 , P12R452 , X12R452 , XL2L452

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A blue ink handwritten signature, appearing to be "H.A.J. van Dartel", written over a light grey background.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

ABUS Pfaffenhain GmbH
Number: 466.312.07

page 2 of 2

1. PRODUCT
euro profile cylinder

PRODUCT TYPE
cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical operation
Construction: double OR single with various couplings
with OR without fracture line
with OR without activation pawl on the 2nd key option STD: standard function
GKUP: emergency and hazard function
PKUP: freewheel function
System: horizontal key profile
1 row 6 mechanical operated retainers +
1 row of 6 blockelements
Material: cylinder body: brass with various coatings
Dimension: 17 mm profile from 28 mm in various extensions per 5 mm
Fixing: 1 steel bolt M5, length . backset + 10 mm
Intended use: in combination with cylinder mortice locks and security furniture

3. DELIVERY

The delivery includes an installation instruction:
EK-DR-0051-06.2020

4. PERFORMANCES

A euro profile cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
